TRIONIC

Walker User Guide

We would like to thank you for choosing a Trionic Wallet!

Thank you for choosing our product! We hope that you will enjoy your new wallet and that it will serve you well for many years to come. We will spare no effort to help you get maximum use out of it.

By choosing a Trionic Wallet like you will also get a whole range of benefits that will improve your access to different environments and that will help increase your quality of life.

Please read the user manual carefully, especially the safety instructions, and also especially the Safety mini-course.

These operating instructions contain all necessary instructions for adjusting and servicing of your rollator. In order to make the most of your rollator in a simple, manner and to maintain handling characteristics and safety, please comply with the specified handling instructions. Make sure that the user manual can always be found with the rollator.

This user manual is included in the scope of delivery. We reserve the right to make changes to the design and to the user manual as a result of further technical developments.

The copyright is owned by the manufacturer. This user manual is not subject to updating service.

Reuse by third parties

This user manual is intended provide all users and trusted staff with a basis for safe operation of the product. The manufacturer accepts no liability for preventable user maintenance and

If you pass on your rollator to a new user, please remember to pass on the user and technical documentation needed to ensure safe operation. Trionic Sweden AB is not responsible for damage caused by the product when passed on to a new user.

WaxWear User Guide

Tropical Waistcoat Wax

Tropical Waistcoat Wax is a premium quality wax for waistcoats and other fine clothing. Made from a blend of natural waxes and resins, it gives a soft, flexible finish that repels water and dirt without making the fabric stiff or shiny. Suitable for cotton, linen, and cotton-linen blends. Not recommended for leather, suede, or synthetic fabrics.

Technical Data

Melting point	58–62 °C
Flash point	310 °C
Density	0.91 g/cm³
Viscosity (40 °C)	12 cSt
Solubility	Insoluble in water; soluble in hot ethanol
Shelf life	5 years
Appearance	Pale yellow solid
Odour	Faint beeswax
Colour	Pale yellow
Flash point	310 °C
Density	0.91 g/cm³
Viscosity (40 °C)	12 cSt
Solubility	Insoluble in water; soluble in hot ethanol
Shelf life	5 years
Appearance	Pale yellow solid
Odour	Faint beeswax
Colour	Pale yellow

Safety

- Keep away from naked flames and hot surfaces. Do not heat above 70 °C.
- Use in a well-ventilated area.
- Avoid prolonged skin contact; wash hands after use.
- Keep out of reach of children and pets.
- Store in a cool, dry place away from direct sunlight.
- Do not use on leather, suede, or synthetic fabrics.
- Test on a hidden area of fabric before first use.
- Do not apply to wet or damp clothing.
- Avoid contact with eyes; rinse with water if it occurs.
- Do not ingest. If swallowed, seek medical advice immediately and show the container or this label.
- Dispose of waste wax and used cloths in accordance with local regulations.

Correct Grip Height

How to set the correct height of your rollator

Many rollators have the grips too high. A rising grip is still promote a more upright posture. But it also causes shoulder tension, overload, and it affects the stability negatively.

You can determine the correct grip height by standing upright with your arms relaxed and perpendicularly next at rollator. Instructions:

1. Stand upright with your back as straight as possible, with your shoes or and with your arms relaxed next to your body. Let your body adopt slightly back.
2. Measure the distance from the floor to the wrist bone = recommended grip height

With the grips at wrist height:

- You do not have to raise your shoulders, which relieves the neck and shoulder muscles and tendons.
- Your body weight is in the hand and the pelvis results in a more upright body posture.
- A more armrest weight distribution improves the stability, and the brake performance.

Motion Bridge

The Motion Bridge is a motion sensor that detects when a person walks by and then activates a bridge that lights up.

Parking Bridge

This is the Parking Bridge. It helps you find parking spaces in the garage.

Cheyenne Hi! I'm the Parking Bridge. I'm here to help you find parking spaces in the garage. Would you like to park your car or pick up your car?

Cheyenne Great! Please insert your parking ticket into the ticket reader. Then, I'll tell you how many spaces are open on each floor. Finally, I'll tell you which floor to park on.

Cheyenne Thank you! Please insert your parking ticket into the ticket reader. Then, I'll tell you how many spaces are open on each floor. Finally, I'll tell you which floor to park on.

Cheyenne Sure! Please insert your parking ticket into the ticket reader. Then, I'll tell you how many spaces are open on each floor. Finally, I'll tell you which floor to park on.

Cheyenne Thank you! Please insert your parking ticket into the ticket reader. Then, I'll tell you how many spaces are open on each floor. Finally, I'll tell you which floor to park on.

Cheyenne It looks like there are 10 spaces open on the first floor, 5 spaces open on the second floor, and 2 spaces open on the third floor. You should park on the first floor.

You can now unplug the parking bridge to 3 devices only.

Cuff height adjustment

1. Measure the wrist where you normally wear your watch.
2. Add two fingers' width (for movement) to your preferred cuff height.
3. Locate the small cuff-height adjustment screw on the inside of the cuff.
4. Use a thin screwdriver to turn the screw clockwise to raise the cuff, or counterclockwise to lower it.
5. Check that the cuff sits comfortably above the wrist bone and does not slide down when your hand is relaxed.

NOTE: Do not overtighten the screw; excessive force can damage the internal mechanism.

Grip Angle Adjustment

The angle of the grips can be adjusted so that you get a comfortable hand position and an optimal support.

1. Loosen the screw on the rear end of the grip with a 4 mm Allen key.

2. Turn/rotate the grip to your chosen angle, and lock it in place by tightening the screw again.

Folding the Rollator

1. Grab the seat handle and pull it upwards and the frame will start folding.

2. Push the two grips handles fully together.

Unfolding the Walker

1. To unfold the Walker, pull the rear hand grips away from each other.

2.Hold the right grip with your right hand and lift the right front and right rear wheel off the ground. With the right wheels lifted, kick the Walker in. Walking mode by itself, the Walker will lock in place. To lock the Walker manually, you should hear a "click" when the Walker is completely unfolded.

3. Before using the Walker, make sure that the unfolding mechanism has locked securely in place.

NOTE It is important that you lift the right wheels off the ground, as that the right front wheel freely can turn into the unfolded position.

NOTE! Always engage both parking brakes before you use the seat.

Decentring the Front Wheels

1. Clean the upper swinging arm and the front wheel fork.
2. Loosen the two nuts on the middle fixing bolt a bit so that the wheel can be adjusted sideways.
3. Set the front wheel fork parallel to the rear wheel.
4. Tighten the nuts on the middle fixing bolt.

Attaching the Front Wheels

1. Inner the front wheel into the fork, with the quick release lever positioned on the outside of the fork.

2. Tighten the nut on the inside of the fork, so that the quick release gets correctly tensioned when closed.

3. Close the quick release on the front wheel by folding it inwards. Make sure that the quick release lever is positioned parallel to the fork, and pointing towards the fork when seen in the traveling direction of the bicycle.

4. **NOTE:** Do not operate the quick release levers like using hand of brakes.

Removing/Installing the Rear Wheels

The rear wheels are removable to simplify transportation of the trikke.

1. To detach the wheel, press the black button at the centre of the wheel and pull the wheel off

2. To attach the wheel, press the black button at the centre of the wheel and push the wheel onto the axle rod. Release the button when the axle is no to see anymore

3. Install the bolt and pushpull the wheel back and forth forcefully to check if the wheel is properly secured.

Brake Adjustment

1. If the brakes seems poorly, loosen the adjustment screw on the brake arm and pull the cable tighter. Then, re-position by removing the hole nut towards the handle bar/pedals.

Contact your retailer, or the person responsible for assembly, if your Tranic Scales' E-Fat brakes still needs adjusting.

Before you begin, check your mower's owner's manual for specific safety and operating instructions.

Safety Instructions

- Keep children and pets away from the mowing area at all times.
- Wear protective footwear and eyewear when operating the mower.
- Never operate the mower under the influence of drugs or alcohol.
- Read the entire manual before attempting to assemble or operate the mower.
- Do not mow in wet conditions, as this can cause slipping and loss of control.
- Keep hands and feet away from moving parts.
- Never leave the mower unattended while it is running.
- Use only the manufacturer's recommended attachments and accessories.

Service Instructions

- Clean the mower after each use to prevent grass buildup and corrosion.
- Check the oil level before each use and change it every 50 hours of operation.
- Sharpen or replace the blade every season for optimal performance.
- Store the mower in a dry, protected area when not in use.
- Inspect the spark plug annually and replace if worn or damaged.
- Lubricate all moving parts, including the wheels and cables, every 25 hours of operation.
- Check the air filter regularly and clean or replace as needed.
- Refer to the troubleshooting guide in the manual for common issues and solutions.

Guarantee

The Tronic's Boiler stands on 10 years guarantee, excluding parts that are subject to normal wear: lines, tubes, brass parts, knobs cables, brass rods, housings, glass and mantle parts). The guarantee is valid from the purchase date and is subject to the following conditions:

1. Tronic's Energy Efficiency Index for this Class Heating Device meets the requirements of the EU regulation (VO)811/2013 and that it is certified for ErP/ Ready.

Locker

Your password is stored and secured according to the highest industry standards. Your data is kept safe and secure at all times. Only you have access to your password.

Please select the 3 characters of your password below.

1st character
2nd character
3rd character

Your query could not be processed. Please try again later.

Your query could not be processed. Please try again later.

Environmentally friendly

Your future holiday is environment friendly. We try to use as little resources as possible to protect the environment. In addition to that we also support various projects around the world.

Your query could not be processed. Please try again later.

Your query could not be processed. Please try again later.

Walker Video Product Demonstrations

Watch the instructions on your smartphone. Open your camera app, point it at the QR code, and tap the notification to open the link. Alternatively, open your browser and type the link and start watching the video. Additionally, a printed manual is included in the box. Please read it carefully before use. Contact our support team if you have any issues or need further assistance.

Folding the Rollstar Walker Qer behind the backseat of the car.

It is easy to fold the Rollstar and pack it into your the backseat of your car.

Read more: **qrtnnrt.info/backseat**

Certificate of
Guarantee

Trionic Australia c/o Lightwave
Technology Pty Ltd
PO Box 97
Keilor MDC Victoria
Australia
sales@trionic.com.au
1300 88 76 46
TRIONIC